

Orchard Burma Bridge Installation Instructions ORU050/ORW050

Burma Bridge Installation Instructions



- 1 Read all instructions carefully before starting the assembly.
- 2 Check using the parts list and fixing kit list that none of the components are mssing. If any parts are missing contact our Sales Office.
- 3 Plan the final position of the play equipment ensuring there is sufficient space. See the ground plan for recommended safety surfacing area and critical fall heights to EN1176.
- 4 Excavate the foundation holes in accordance with the plan. Orchard is designed to be installed onto a level site.
- 5 Fit the ground fixings OPA001/OPA002 to the bottom of the relevant logs, following the instruction sheet on page 04.
- 6 Erect the main logs into the foundation holes using the ground plan for reference. Each log is numbered at the top, and marked at the base with an X.
- 7 Assemble the activities to the logs prior to concreting into position.
- 8 When all the activities are fitted, fill the foundation holes to the required depth with concrete.
- 9 Do not allow the equipment to be used until the concrete has set (2 3 days) and the required safety surfacing has been installed.
- 10 Check that all fixing bolts are fully tightened. Fit the post caps following the instruction sheet on page 04.
- 11 After one month check all bolts and tighten if necessary. After this one month period insert the rubber log plugs as described on the instruction sheets page 05 and 06.
- 12 Follow the maintenance instructions supplied.

During installation care must be taken to prevent hazards to children. Care should be taken if conditions are abnormal.

Ref Description OPA001/002 Ground Fixing ORA030 2.7M Burma Bridge ORA040 Bracing Leg OPU050 Logs (set of 6) ORU050F Fixing Kit

OPU050 -ORA040 OPA001/002 **ORA030**

ORU050/ORW050 Burma Bridge Parts List


Teldo Hillows of the state of t





FIT RUBBER CAPS TO THE END OF THE LOGS AND FIX IN POSITION USING 3 OFF WDS450 PER JOINT.

NOTE THE RUBBER CAPS ARE A TIGHT FIT ON THE LOGS.




PARTS PER JOINT		
STOCK CODE	DESCRIPTION	QTY
ORS003	RUBBER POST CAP	1
WDS450	12 x 2" CSK POZI SCREW	3

GROUND FIXINGS

IMPORTANT NOTE

INSERT THE LOGS INTO THE GROUND FIXINGS 200MM ONLY. THE BOTTOM OF THE LOG SHOULD LINE UP WITH THE TOP VENTILATION HOLES.




BASE OF THE LOG MAKED WITH AN X.

OPA001 GROUND FIXING FOR WET POUR (SHOWN) OPA002 GROUND FIXING FOR LOOSE FILL

PARTS PER GROUND FIXING			
STOCK CODE	DESCRIPTION	QTY	
HSS530	M10 x 100 COACH SCREW BZP	3	
OPA001/002	ALLOY GROUND FIXING ANODISED	1	




LOG JOINTS



IMPORTANT NOTE TWIST THE RUBBER SPACERS SO THAT THEY ARE FLUSH AGAINST THE LOGS.


7		
	PARTS PER LOG JOINT	
STOCK CODE	DESCRIPTION	QTY
HHB770	M16 x 260 HEX HEAD BOLT	1
LKN340	M16 NYLOC NUT	1
ORS001	TIMBER RUBBER SPACER	2
ORS002	35 DIA RUBBER LOG PLUG	2
ORS005ZP	METAL SPACER RING ZINC PLATED	1
WSR034	M16 FLAT WASHER FORM C	2

ROPE FIXINGS




	PARTS PER ROPE JOINT	
STOCK CODE	DESCRIPTION	QTY
LKN340	M16 NYLOC NUT	1
ORS002	35 DIA RUBBER LOG PLUG	1
WSR034	M16 FLAT WASHER FORM C	1





ACTIVITY FIXING



	PARTS PER FIXING	220
STOCK CODE	DESCRIPTION	QTY
HHB720	M16 x 120 HEX HEAD BOLT	1
ORS002	35 DIA RUBBER LOG PLUG	1
WSR034	M16 FLAT WASHER FORM C	1

ORU050F Fixing Kit



9			
STOCK CODE	DESCRIPTION	QTY	
A	M16 x 120 HEX HEAD BOLT	10	
HHB720			
111111111111111111111111111111111111111	M16 x 260 HEX HEAD BOLT	6	
HHB770	1440 00 00 10 10 00 00 10 10 10 10 10 10 10	4.5	
	M10 x 80 COACH SCREW	15	
HSS530			
1100000	M16 NYLOC NUT	8	
6			
LKN340			
	TIMBER RUBBER SPACER	10	
ORS001			
	41 DIA RUBBER LOG PLUG	20	
ORS002			
	ORCHARD RUBBER POST CAP	8	
ORS003			
	SPACER RING ZINC PLATED	5	
ORS005ZP			
ONOUUZF	No12 x 2" CSK POZI SCREW	27	
•			
WDS450			
WSD034	M16 FLAT WASHER	23	
WSR034			

Burma Bridge Maintenance Instructions

NOTE

The warranty is invalidated if these instructions are not followed.

All wood needs annual inspection and retreatment where required.

Recommended Regular Inspection and Maintenance		Inte 14	rval D 28	ays 56	365
Check stability of structure, tighten connections if required.					
Check all uprights at ground level for corrosion and/or rot. Replace any defective parts.					
Check all painted elements for damage, rub down and repaint or replace as required.					
Check chain/ropework assemblies for wear and damage, replace if required.					
Check rotating and pivot points for wear and smooth running lubricate or replace if required.					
Check rubber parts for wear and/or damage, replace if required.					
Check tension cables, adjust if required.					
Check wear of cables, replace if required.					
Check slide chutes for smoothness and any foreign elements, remove any found.					
Check rubber safety surfaces for damage and poor performance, repair or replace if required.					
Check loose fill safety surfaces, remove any foreign elements, rake level and top up if required.					

Suiclifie Play

Disposal Instructions

All components should be broken down into categories of:-

- 1 **Mild Steel** all Swing Frames, Playzone, Toddlerzone, Teenzone activities, Mission, Orchard Deck Frames and Springie Frames.
- 2 Stainless Steel all Slides, Mirror Panels.
- 3 Aluminium all Playzone, Mission and Toddlerzone Posts.
- 4 Galvanised Steel all Chains and Teenzone Posts.
- 5 **Moulded Rubber Products without steel inserts** all Mission and Toddlerzone Caps and edge details.
- 6 Timber all natural timber, plywood, and MDF panels.

Wherever possible these materials should be taken to specialist recycling organisations and recycled. In some cases where composite materials are used, then disposal at land fill sites is the only alternative such as:

- 7 Moulded Rubber Products encasing steel inserts all Swing Seats, Deck Tops, Duo/Dizzy Disc Tops.
- 8 **High Pressure Laminate** all Toddlerzone, Playzone and Teenzone Panels.
- 9 Steel Core Polypropylene Rope all Scramble Nets, Space Nets, Playzone/Toddlerzone/Mission Ropes.